

1. UNIQUE IDENTIFICATION CODE OF PRODUCT TYPE:

REABILITA CAL RB.

2. TYPE, LOT OR SERIAL NUMBER:

Renovation Mortar (R).

The lot number is printed on the package.

3. PREDICT USES ACCORDING TO EM 998-1:

Industrial mortar of inorganic binders for internal and external rendering of walls and ceilings.

4. NAME, COMMERCIAL DESIGNATION AND MANUFACTURER'S CONTACT:

Secil Martingança, S.A.

Apartado 2 EC Maceira

2406-909 Maceira LRA

Commercial Designation: SECILTEK

5. NAME AND CONTACT OF REPRESENTATIVE:

Not applicable.

6. EVALUATION AND VERIFICATION SYSTEM OF THE REGULARITY OF PRODUCT PERFORMANCE:

System 4.

7. HARMONIZED STANDARD:

EN 998-1

SECILTEK conducted the determination of the product type based on the type methods, calculations, on the listed values and factory production control.

8. EUROPEAN TECHNICAL EVALUATION:

Not applicable.

PERFORMANCE DECLARATION

DOP.03002

Version: 1.0/EN

Review date: February / 2019

SECIL TEK
DÁ FORMA ÀS IDEIAS

Print date: February 1st, 2019

9. DECLARED PERFORMANCE

Essential Characteristics	Performance	Harmonized Technical Specifications
Compressive strength (class)	CS II	EN 998-1
Adhesion to brick and block /Fracture mode	0.2 N/mm ² / B	
Capillary water absorption after 24 hours	≥ 0.3 kg/m ²	
Water penetration after capillary testing (mm)	< 5 mm	
Water vapour permeability	μ ≤15	
Reaction to fire	Class A1	
Thermal conductivity (listed value)	(λ 10, dry) 0.61 W/m.K (P= 50%)	
Durability	Until there is a standard test, the assessment is based on provisions validated at the location of the mortar use	

10. THE PERFORMANCE OF THE PRODUCT IDENTIFIED I NUMEBERS 1 AND 2 IS IN ACCORDANCE WITH THE PERFORMANCE DECLARED IN NUMBER 9. THE PRESENT DECLARATION OF PERFORMANCE IS ISSUED UNDER TE EXCLUSIVE RESPONSIBILITY OF THE MANUFACTURER IDENTIFIED IN NUMBER 4.

Signed by and in name of the manufacturer
by:



Dina Frade

(Operational Direction)

Maceira, February 1st, 2019