PERFORMANCE DECLARATION

DOP.03013

Version: 1.0/EN

Review date: February / 2019



Print date: February 1st, 2019

1. UNIQUE IDENTIFICATION CODE OF PRODUCT TYPE:

REABILITA RR 20.

2. TYPE, LOT OR SERIAL NUMBER:

General purpose rendering/plastering mortar (GP). The lot number is printed on the package.

3. PREDICT USES ACCORDING TO EM 998-1:

Industrial mortar of inorganic binders for internal and external rendering of walls and ceilings.

4. NAME, COMMERCIAL DESIGNATION AND MANUFACTURER'S CONTACT:

Secil Martingança, S.A. Apartado 2 EC Maceira 2406-909 Maceira LRA

Commercial Designation: SECILTEK

5. NAME AND CONTACT OF REPRESENTATIVE:

Not applicable.

6. EVALUATION AND VERIFICATION SYSTEM OF THE REGULARITY OF PRODUCT PERFORMANCE:

System 4.

7. HARMONIZED STANDARD:

EN 998-1

SECILTEK conducted the determination of the product type based on the type methods, calculations, on the listed values and factory production control.

8. EUROPEAN TECHNICAL EVALUATION:

Not applicable.



PERFORMANCE DECLARATION

DOP.03013

Version: 1.0/EN

Review date: February / 2019



Print date: February 1st, 2019

9. DECLARED PERFORMANCE

Essential Characteristics	Performance	Harmonized Technical Specifications
Adhesion to brick and block /Fracture mode	0.2 N/mm ² /A and B	
Capillary water absorption	Class W1	
Water vapour permeability	μ≤15	
Reaction to fire	Class A1	EN 998-1
Thermal conductivity (listed value)	(λ 10, dry) 0.45 W/m.K (P= 50%)	
Durability	Until there is a standard test, the assessment is based on provisions validated at the location of the mortar use	

10. THE PERFORMANCE OF THE PRODUCT IDENTIFIED I NUMEBERS 1 AND 2 IS IN ACCORDANCE WITH THE PERFORMANCE DECLARED IN NUMBER 9. THE PRESENT DECLARATION OF PERFORMANCE IS ISSUED UNDER TE EXCLUSIVE RESPONSIBILITY OF THE MANUFACTURER IDENTIFIED IN NUMBER 4.

Signed by and in name of the manufacturer by:

Dina Frade

(Operational Direction)

Maceira, February 1st, 2019

