

REDUR PK 02

FINE SYNTHETIC FINISH

1. DESCRIPTION

REDUR PK 02 is a synthetic stucco, produced with acrylic resins in aqueous dispersion, ready-to-use.

2. FIELD OF USE

REDUR PK 02 is a product intended to provide a smooth finish to indoor and outdoor walls and ceilings. It is used over hydraulic renders or in texture renovation operations over *REABILITA RS 34*, followed by painting.

REDUR PK 02 resists to the proliferation of fungi and contributes to the reduction of dirt accumulation.

For non-current uses or on particular substrates, we advise you to contact our Technical and Commercial Service.

3. PRODUCT CHARACTERISTICS

Paste product	Value
Aspect	Slightly satin white paste
Density at 25 °C	1,80 to 1,84 kg/dm ³
Theoretical consumption	1,4 kg/m ² /mm
Maximum thickness per layer	1 mm
Maximum thickness	2 mm
Waiting time between layers	2 to 4 hours
Waiting times for painting	7 days

Recommended waiting times refer to the application of the product under normalized temperature and humidity conditions.

4. APPLICATION

a) Substrate preparation

Substrates should be free from dust, release agents, loose or unstable materials, efflorescence, as well as any type of material that affects the normal conditions of adhesion.

The substrate must be levelled, completely dry and hardened. In case of new plasters, they should be levelled and trowelled with their cure completed.

In case the substrate needs levelling, the *REABILITA RS 34* regularization and renovation mortar should be used.

REDUR PK 02

FINE SYNTHETIC FINISH

b) Application

Prior to application, the product should be homogenized in the bucket and mixed briefly.

REDUR PK 02 should be spread in a very thin and uniform layer with a smooth metal trowel so as to fill all surface pores of the base. It should be applied in as many coats as needed for the intended finish.

The drying time per coat is 2 to 4 hours under normal conditions of temperature and humidity. Between layers, the surfaces should be properly sanded.

Before applying the finish with an aqueous base paint, let **REDUR PK 02** to dry at least 7 days.

c) Restrictions

REDUR PK 02 should not be applied at room and substrate temperatures below 5 °C and above 30 °C and air relative humidity of more than 70 %.

Low temperatures and high relative humidity delay the drying of **REDUR PK 02**.

Application of **REDUR PK 02** should not be carried out when atmospheric conditions are adverse to the application and drying process such as:

- Frozen substrates;
- Substrates that are too hot;
- In case of rain or forecast of rain or showers, for 48 hours after application is completed;
- In the presence of strong, hot and dry wind; under direct, intense sun radiation. If possible, facades should be protected, so as to minimize the action of elements.

d) Complementary Advices

Do not add any other products to the product. **REDUR PK 02** should be applied as it is shown in its original packaging.

5. PACKAGING AND VALIDITY

Packaging

7 kg and 25 kg buckets in plasticized pallets of 30 or 24 buckets, respectively.

Validity

12 months provided the conditions of the original packaging remain unaltered and in good storage conditions, protected from extreme temperature and humidity.

6. HEALTH AND SAFETY

(DOES NOT REPLACE CONSULTATION OF THE PRODUCT SAFETY DATA SHEET)

- Causes skin burns and serious eye damage;
- May cause an allergic skin reaction;
- Harmful to aquatic life with long lasting effects;
- Toxic if swallowed, in contact with skin or if inhaled;
- If it is necessary to see a doctor, show him the package or the label;
- Keep out of children's reach;
- Wash thoroughly after handling;
- Use protective gloves / protective clothing / eye protection / face protection;
- IF IT IS SWALLOWED: rinse mouth. DO NOT induce vomiting;
- IF IT COMES IN CONTACT WITH SKIN (or hair): immediately remove all contaminated clothing. Rinse skin with water / take shower;
- IF IT COMES IN CONTACT WITH EYES: rinse thoroughly with water for several minutes. If you wear contact lenses, remove them if possible. Continue to rinse;
- Dispose of the contents and / or the container by means of the selective collection system used in your municipality.

Being the conditions of applying our products out of our reach we do not take responsibility for its misuse. It is the customer's duty to verify the suitability of the product for the intended purpose. In any case, our responsibility is limited to the value of the goods supplied by us. The information contained in the present data sheet may be altered without prior notice. In case of doubt and if you need any further advice please contact our Technical Services.

*Revision of January 2019
FT 02011.01 EN*