

ISOVIT AD 41

SUBSTRATE CLEANING SOLUTION

1. DESCRIPTION

ISOVIT AD 41 is a cleaning product for mineral and acrylic substrates.

2. FIELD OF USE

ISOVIT AD 41 is used as exterior surface treatment. It is suitable for application on mineral substrates such as cement, stones and ceramic tiles. It may also be applied on acrylic substrates, being properly diluted.

ISOVIT AD 41 is a broad application cleaning product. Its low viscosity allows it to penetrate the pores ensuring greater efficiency.

3. PRODUCT CHARACTERISTICS

Characteristics	Value
Colour	Colourless
Density at 20°C	1,1 kg/l
Solvent	Water
Theoretical yield	1 l / 5 to 6 m ² / coat

4. APPLICATION

a) Substrate preparation

ISOVIT AD 41 should be applied after washing the surfaces to be treated with water jet so as to remove all dirt and dust that may hinder its performance.

When applying the product, the surface to be treated may be dry or slightly wet.

b) Application

Before application, *ISOVIT AD 41* should be homogenised, by stirring.

Apply *ISOVIT AD 41* evenly and leave it for 15 to 30 minutes with sprayer, either mechanical or manual.

Once the product has its effect, clean the walls with water jet.

c) Restrictions

ISOVIT AD 41 should not be applied in rain, strong sunlight or when substrate is hot or frozen. Application should not be carried out at ambient temperatures below 0 °C.

ISOVIT AD 41

SUBSTRATE CLEANING SOLUTION

d) Complementary Advices

The consumption of **ISOVIT AD 41** should be respected as stated above, to ensure its performance.

Do not add any other products to **ISOVIT AD 41**. It should be applied as it is shown in its original packaging.

When still fresh, tools may be cleaned with water.

5. PACKAGING AND VALIDITY

Packaging

5 litres jerrican.

Validity

24 months provided the conditions of the original packaging remain unaltered and in good storage conditions, protected from extreme temperature and humidity.

6. HEALTH AND SAFETY

(DOES NOT REPLACE CONSULTATION OF THE PRODUCT SAFETY DATA SHEET)

- Causes severe burns;
- Irritating to eyes, respiratory system and skin;
- May cause sensitization in contact with skin;
- Do not breathe dust;
- Avoid contact with skin and eyes;
- If it comes in contact with eyes, rinse immediately and thoroughly with water and seek a specialist advice;
- Use protective clothing and gloves, as well as eye protection equipment;
- Keep out of children's reach.

Being the conditions of applying our products out of our reach we do not take responsibility for its misuse. It is the customer's duty to verify the suitability of the product for the intended purpose. In any case, our responsibility is limited to the value of the goods supplied by us. The information contained in the present data sheet may be altered without prior notice. In case of doubt and if you need any further advice please contact our Technical Services.

*Revision of March 2019
FT 13008.01 EN*